

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 500.35180CX1

First Inventor or Application Identifier Takeshi Aimoto

Title See 1 in Addendum

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 35]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 4]
4. Oath or Declaration [Total Pages 2]
 - a. ☐ Newly executed (original or copy)
 - b. ☒ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure Statement (IDS)/PTO-1449 [Copies of IDS Citations]
11. ☒ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) filed in prior application
(PTO/SB/09-12) [Status still proper and desired]
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. 08/788,416

Prior application information: Examiner Nguyen, K. Group / Art Unit: 2731

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label 020457 or ☐ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name					
Address					
City	State	Zip Code			
Country	Telephone	Fax			

Name (Print/Type)	David S. Lee	Registration No. (Attorney/Agent)	38,222
Signature	David S. Lee	Date	02/14/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s): AIMOTO, et al.
Serial No.: Continuation of U.S. Serial No.
08/788,416
Filed: February 14, 2000
For: PACKET SWITCHING DEVICE AND CELL
TRANSFER CONTROL METHOD
Group: Unassigned
Examiner: Unassigned

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

February 14, 2000

Sir:

The following amendments and remarks are respectfully
submitted prior to the Rule 53(b) Continuation Application
filed on even date.

IN THE SPECIFICATION

Please insert before the first line of the
specification the following:

-- This is a continuation of application Serial No.
08/788,416, filed January 27, 1997, which was allowed on
November 2, 1999. --

004720"07E00000

IN THE CLAIMS

Please cancel claims 12-28 without prejudice or disclaimer.


REMARKS

Entry of the above amendments is respectfully requested. Claims 1-11 and 29 remain pending for examination. Favorable consideration is respectfully requested.

Please charge any shortage in fees due in connection with the filing of this paper, or credit any overpayment of fees, to the deposit account of Antonelli, Terry, Stout & Kraus, LLP, Deposit Account No. 01-2135 (Case No. 500.35180CX1).

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



David S. Lee
Registration No. 38,222

DSL/dbp
(703) 312-6600

PACKET SWITCHING DEVICE AND CELL
TRANSFER CONTROL METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a packet switching device and a fixed length packet transfer control method, and more particularly to an ATM (Asynchronous Transfer Mode) packet switching device having a congestion control function and a cell transfer control method in an ATM network.

Description of the Related Art

10 The transfer of fixed length packets (hereinafter referred to as a "cell") is described, for example, in "Data Communication Using ATM: Architectures, Protocols, and Resource Management", IEEE Communication Magazine, August 1994, p24-33 and
15 "SVC Signaling: Calling All Nodes", DATA COMMUNICATIONS, June 1995, p123-128, and so on.

In an ATM network, a call (connection) is set up by signaling processing performed upon initiating the call along a communication path from a transmitting
20 device (source terminal) to a receiving device (destination terminal) through a switching device (switch) serving as a transfer path of user cells, and the transfer of the user cells is controlled based on

0950410 0440
00429"07E0550

connection identification information attached to a header portion of each user cell.

A call setup procedure is described, for example, in ITU-T Standard Q.2931, and the call setup
5 procedure is executed to set connection information to a transmitting device, each node (switch) on a path, and a receiving device. The connection information includes identifiers for identifying a call on each of links between the transmitting device and a switch,
10 between switches, and between a switch and the receiving device, a traffic class indicative of a priority of cell transfer in a switch, and so on. The identifiers for identifying a connection (call) are referred to as "VPI" (Virtual Pass Identifier) and
15 "VCI" (Virtual Connection Identifier) and set in a header portion of each cell as address information.

Each switch searches for connection information necessary for the switching operation based on VPI and VCI in each of input cells received through
20 a transmission path. The connection information includes, for example, internal routing information (output port number), identifiers to be attached to an output cell (output VPI/VCI), a traffic class indicative of a cell priority in the switch, and so on.

25 The traffic class indicative of a cell priority is described, for example, in "Multimedia Traffic Management Principles for Guaranteed ATM

004720-011E0560

Network Performance", IEEE JOURNAL ON SELECTED AREAS IN COMMUNICATIONS, Vol. 8, No. 3, April 1990, p437-446, and "Traffic Management for B-ISDN Services" IEEE Network, September 1992, p10-19.

5 The traffic class indicative of a cell priority includes two: CBR (Constant Bit Rate) and VBR (Variable Bit Rate). CBR is a traffic class in which a predetermined cell transfer rate is contracted between a network and a terminal upon setting up a call so that
10 the network side guarantees the cell transfer at the contracted transfer rate. VBR is a traffic class which tolerates a certain degree of statistical variations for a transfer rate contracted with a terminal. The scheme which controls traffic with a contract
15 previously made between a network and a terminal is referred to as "preventive control".

As traffic for transmitting cells utilizing a remaining portion of a bandwidth allocated to another terminal in the above-mentioned CBR and VBR without
20 making a special contract related to the transfer rate between a network and a terminal upon setting up a call, there is a group of traffic classes referred to as "best effort control". The transfer rate contract is not made primarily because it is difficult for a
25 terminal outputting burst traffic to predict the characteristic of the traffic upon setting up a call.

The group of best effort control traffics includes a UBR (Unspecified Bit Rate) traffic class in

A configuration of a switch for controlling a transfer in accordance with a traffic class is described, for example, in JP-A-6-197128. In a packet switching scheme described in this publication, each output port is provided with two output buffers, one for CBR traffic class and the other for VBR traffic class, and information indicative of an empty/full state of the two buffers are stored as table information corresponding to each output port, such that an input buffer control unit references the table information to determine a buffer for accumulating cells destined to each output port.

In this case, the output priority of cells accumulated in CBR buffer is ranked higher than that of the VBR buffer so that a communication delay time in a switch can be limited within a predetermined value for a group of cells of the CVR traffic which has strict restrictions to communication delay. In addition, if the CBR buffer does not have any free space, for

example, cells may be accumulated in the VBR buffer, provided that it has some free space, to make good use of a bandwidth in the switch. Further, for supporting the ABR and UBR traffic classes, an output buffer supporting further traffic classes may be additionally provided in addition to the CBR and VBR traffic classes.

SUMMARY OF THE INVENTION

As described above, while several traffic classes have already been proposed in asynchronous communication, it is desired to perform a transfer control by further fractionizing the characteristics in each traffic class, in addition to controlling how a plurality of these traffic classes are properly used.

However, taking as an example the UBR traffic classes which do not give special guarantee to a cell transfer, when a network falls into congestion, a conventional system does not have any means for controlling the Quality of Service belonging to these traffic classes.

It is an object of the present invention to provide a packet processing apparatus and an ATM cell transfer control method which can control the Quality of Service when congestion occurs for a group of best effort control traffic classes which do not make a contract with respect to a transfer rate between a network and a terminal upon setting up a call.

It is another object of the present invention to provide a node such as an ATM switching device and an ATM cell transfer control method which can control selective cell discard when congestion occurs for a
5 group of traffic classes which have difficulties in making bandwidth reservation from a terminal device upon setting up a call.

To achieve the above objects, a cell transfer control method of the present invention storing
10 information indicative of a priority related to cell discard declared from a source unit in any of nodes in the network corresponding to an identifier of the connection, when setting up a connection belonging to a particular traffic class which does not make bandwidth
15 reservation, such that, when congestion occurs on the connection, the node performs selective discard processing on cells belonging to the particular traffic class in conformity to a predetermined discard condition determined by a relationship between the
20 status of the congestion and the priority.

The node stepwisely changes a cell discard priority class, for example, in accordance with the congestion status, and determines whether or not each cell belonging to the particular traffic class is
25 discarded in conformity to a predetermined discard condition determined by the priority and the cell discard priority class.

In this case, the node may judge whether or not a data block included in a data portion of each cell of the particular traffic class is divided from the same transmission message as a data portion of a previous cell, and perform the discard processing on cells falling under the discard condition in units of transmission message.

As for the cell discard in units of message, the discard processing is started on cells which fall under a predetermined discard condition determined, for example, by a relationship between the congestion status and the priority, and the discard processing is continued on subsequent cells including part of the same transmission message as data portions of already discarded cells, even if the subsequent cells deviate from the discard condition due to a change in the congestion status. As a modification to the cell discard in units of message, for example, cells including data blocks of the same transmission message as data portions of previously sent cells may be excluded from cells to be discarded, within cells falling under the discard condition, and the discard processing may be started from a cell including a head data block of a subsequent new message.

Also, the present invention provides a packet switching device connected to a plurality of input lines and to a plurality of output lines for

09503110 021400
004220 07E0560

More specifically, the packet switching device of the present invention comprises switch means having a plurality of input ports and a plurality of output ports for transferring a fixed length packet (cell) inputted from each input port to any output port determined by cell header information, input line interfaces each connected between one of the input ports and an input line, output line interfaces each connected between one of the output ports and an output line, a call control unit connected to the switch means and each of the input line interfaces for transmitting

More specifically, the packet switching device of the present invention comprises switch means having a plurality of input ports and a plurality of output ports for transferring a fixed length packet (cell) inputted from each input port to any output port determined by cell header information, input line interfaces each connected between one of the input ports and an input line, output line interfaces each connected between one of the output ports and an output line, a call control unit connected to the switch means and each of the input line interfaces for transmitting

and receiving a call control cell to and from the switch means and for transmitting control information including header rewrite information to each of the input interfaces, and congestion monitor means for
5 detecting a congestion status of output cells on each of the output ports and notifying each of the input interfaces of a detected congestion status as congestion status information, and is characterized in that the call control unit includes means, operative
10 when setting a connection belonging to a particular traffic class which does not make bandwidth reservation, for notifying an input interface accommodating a calling unit, which is a requestor of the connection setup, of identification information on
15 the connection and control information including traffic class information declared by a control message from the calling unit and sub-class information indicative of a priority related to cell discard, and each of the input interfaces includes cell discard
20 control means for selectively discarding user cells belonging to the particular traffic class received from each input line after the connection is set up, in conformity to a predetermined discard condition determined by a congestion status at a destination
25 output port of the user cell revealed from the congestion status information and the priority related to cell discard notified from the call control unit.

004220" 07E0550

Each of the input line interfaces includes header conversion means for rewriting header information of an input cell from each input line, and input buffer means for temporarily accumulating head
5 converted cells, and the cell discard control means selectively accumulates input cells belonging to the particular traffic class in the input buffer means in conformity to the discard condition.

Also, the switch means includes output buffer
10 means corresponding to the each output port, and means for distributing each of user cells having a head converted by the each input line interface to either of the output buffer means specified by header information, and the congestion monitor means detects a
15 congestion status of the output cell from an accumulation situation of user cells in the each output buffer means. In addition, the switch means may include a plurality of output buffer means for each output port so as to allocate one of the output buffer
20 means to cells of a CBR traffic class which guarantees a transfer rate.

According to the configuration of the present invention, the priority information related to cell discard has been previously defined as a sub-class for
25 a traffic class which does not make bandwidth reservation such as the aforementioned best effort control traffic class group. Upon setting up a call, a source terminal notifies a network of the priority such

09503110 021400
004720 0710560

that cells of the connection having the lowest priority
are first discarded in conformity to the priority
information specified by the sub-class, when a best
effort control traffic class falls into congestion, to
5 exclude cells of connections having higher priorities
from cells to be discarded even if the cells belong to
the same traffic class. When the degree of congestion
becomes more grave even though cells have been
discarded, the cell discard is gradually performed on
10 cells of connections having higher priorities.
However, as the best effort traffic class is recovered
from the congestion, the discard processing is stopped
in order from cells of connections having higher
priorities. In this way, the Quality of Service can be
15 guaranteed for connections having higher priorities
even within the best effort control traffic class
group.

The foregoing and other objects, advantages,
manner of operation and novel features of the present
20 invention will be understood from the following
detailed description when read in connection with the
accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram illustrating an
25 embodiment of a packet switching device 100 according
to the present invention;

Figs. 2A, 2B, 2C are diagrams illustrating formats of cells handled by the packet switching device 100 and a control message outputted from a terminal;

Fig. 3 is a block diagram illustrating an embodiment of an output buffer 107 in Fig. 1; and

Fig. 4 is a block diagram illustrating an embodiment of an input line interface 102 unit in Fig. 1.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An ATM switching device comprising FIFO output buffers for controlling cell transfer with the CBR traffic class treated as a traffic having a higher priority will be described as an embodiment of the present invention.

Fig. 1 illustrates an ATM switching device (switch) 100 according to the present invention which is connected to N input lines and N output lines.

While a network configuration including two terminal devices A and B 162, 164 connected to the switching device through input/output lines (subscriber lines) is illustrated for convenience of explanation, a portion of the input/output cables may be a trunk for connecting the switching device to another switching device. Also, in this example, the configuration is illustrated such that the terminal A 162, located on the left side of the switch 100, transfers cells to the

terminal B 164 located on the right side of the switch 100. However, in an actual switching device, an i th input line forms a pair with an i th output line, and an output cell from the first output line in Fig. 1 is

5 inputted to the terminal A, while a transferred cell from the terminal B is inputted to an N th input line.

The switch 100 is composed of a plurality of input line interface units (LIFi) 102 (102-1 ~ 102- N) disposed corresponding to the respective input lines, a
10 switch core unit 120, a plurality of output line interface units (LIFO) 108 (108-1 ~ 108- N) disposed corresponding to the respective output lines, and a call control unit (connection processing unit: CP) 140.

Each of the input line interface units 102 is
15 composed of a header conversion circuit 132, a cell discard judgement unit 136, and a cell buffer 134. Also, the switch core unit 120 is composed of a crossbar switch circuit 105, a plurality of FIFOs 107 (107-1 ~ 107- N) provided corresponding to respective
20 output lines, and a congestion status measurement circuit 106 connected to the respective FIFOs 107.

Fig. 2A illustrates a format of a cell 210 inputted from each input line to the input line interface unit 102 of the switch 100.

25 A message transmitted from the terminal A to the terminal B is divided into a plurality of data blocks having a fixed length, and a cell header is

00500110 021400
004720 07700560

added to each data block to form the cell 210. Each cell 210 includes a header portion and a data portion 212, and the header portion includes an input VCI 216, and information (PTY) 214 indicating the position of a data block included in the data portion within a packet (transmission message) treated by a higher rank protocol. Assume in the following description that a cell including a data block at the head of an upper rank packet is referred to as a "packet delimiter".

10 The header conversion circuit 132, when an input cell 210 is inputted thereto from an input line, reads header conversion information corresponding to the input VCI 216 of the inputted cell 210 from a header conversion table to convert the header into an internal cell 220 in a format illustrated in Fig. 2B.

15 Added to a header portion of the internal cell 220 are an output VCI 221 for replacing the input VCI 216 of the input cell 210, routing information (output port information) 222, a traffic class 224, a sub-class 225, and a packet discard status information 228 indicating whether or not a packet associated with the VCI is discarded or not. Unless congestion occurs at an associated output port, the internal cell 220 is sent to the switch core unit 120 without being
20 discarded, and driven into a particular output buffer FIFO 107 indicated by the routing information (output port information) through the crossbar switch circuit 105.

00420-0720560

Fig. 2C illustrates a control message
(connection information) 230 for setting up a call to
be sent from the source terminal 162 to the switch 100
prior to a communication with the receiving terminal
5 164.

The connection information 230 includes
destination address information 232 for specifying a
destination terminal, traffic class information 234,
sub-class information 236 for indicating a priority
10 relative to cell discard, and terminal protocol
information 238 indicative of an upper rank protocol at
the source terminal. The connection information 230 is
divided into a plurality of fixed-length blocks in the
source terminal, and a cell header is added to each
15 block to be formed into a control cell, having a
similar format to that illustrated in Fig. 2A, which is
then driven into the switch 100.

The control cell is transferred from the
switch core unit 120 to the call control unit
20 (connection processing unit: CP) 140 through a signal
processing means, omitted in Fig. 1. The signal
processing means is provided to assemble the contents
(data block) of a data portion 212 of each control cell
into the original connection information (message form)
25 illustrated in Fig. 2C, and may be configured as part
of the call control unit 140.

The call control unit 140 sets the output VCI
226 allocated to a call, output port information 222

specified by the destination address, and a traffic class 234 and a traffic sub-class 236 extracted from the connection information 230 to a conversion table (not shown) of the header conversion circuit 132

5 connected to the source terminal in a call setup sequence executed in response to the connection information.

When a call (connection) setup is completed between the terminals, the source terminal 162 starts
10 sending cells (user cells) 210 to the destination terminal 164.

Fig. 3 illustrates an exemplary configuration of the FIFO output buffer 107.

The FIFO buffer 107 is composed of two FIFOs
15 301, 302, one for CBR and the other for UBR, and an FIFO control circuit 310. The FIFO control circuit 310 preferentially outputs cells accumulated in the CBR FIFO 301 prior to cells accumulated in the UBR FIFO 302.

20 In a normal state in which no congestion occurs, user cells outputted from each FIFO output buffer 107i are inputted to an associated line output control unit LIFO 108i which discards unnecessary internal header information 222 - 228 and sends the
25 user cell in the output cell format including information elements 212 - 221 onto an output line.

The cell accumulation status (congestion status) in each of two FIFOs 301, 302 for CBR and UBR

traffic classes of each FIFO output buffer is collected
in the congestion status measurement circuit 106
through a signal line 156. The congestion status
measurement circuit 106 edits the cell accumulation
5 status into congestion status information corresponding
to an output port, and notifies each of the input line
interface units 102-1 ~ 102-N of the congestion status
information through a signal line 152. For example,
the congestion status measurement circuit 106
10 classifies the cell accumulation status at each output
port into "no congestion", "light congestion", and
"heavy congestion" and edits the cell accumulation
status as the congestion status information.

Fig. 4 illustrates in detail the
15 configuration of the input line interface unit 102,
particularly, the cell discard judgement unit 136. The
cell discard judgement unit 136 comprises a packet
discard judgement circuit 410, a packet delimiter
detection circuit 420, and a congestion level judgement
20 circuit 430.

The congestion level judgement circuit 430
fetches an output port 222, a traffic class 224, and a
traffic sub-class 225 from among information elements
of each input cell converted into an internal cell
25 format by the header conversion circuit 132, judges
whether or not discard of the input cell is necessary
based on the fetched information and congestion status

information 152 provided from the congestion status measurement circuit 106, and provides the packet discard judgement circuit 410 with a discard control signal 153 in accordance with the judgement result.

- 5 The congestion level judgement circuit 430 utilizes discard sub-class information 432, which is counted up or down in accordance with the congestion status information 152, to determine a mode for the discard control signal 153.

- 10 For example, when the traffic class 224 of an input cell is a best effort traffic class, the congestion level judgement circuit 430 pays attention to congestion status information 152' of a particular output port corresponding to the output port
- 15 information 222 of the input cell within the congestion status information provided from the congestion status measurement circuit 106, and counts down the discard sub-class information 432 corresponding to the particular output port when the congestion control
- 20 information 152' indicates "no congestion", maintains a current value of the discard sub-class information 432 when the congestion control information 152' indicates "light congestion", and counts up the discard sub-class information 432 when the congestion control information
- 25 152' indicates "heavy congestion". Next, the congestion level judgement circuit 430 compares the value of a cell discard priority indicated by the

traffic sub-class 225 of the input cell with the
discard sub-class information 432, and sets the discard
control signal 153 in a "pass mode" when the priority
is larger than the value of the discard sub-class
5 information 432, in a "packet unit discard mode" when
equal, and in a "all cell discard mode" when smaller.

The packet delimiter detection circuit 420
judges PTY 214 of an input cell in the internal cell
format outputted from the header conversion circuit
10 132, and turns on a signal 440 indicative of a
delimiter of a packet when the input cell includes a
head block of the packet in a data portion 212. The
signal 440 is provided to the packet discard judgement
circuit 410.

15 The packet discard judgement circuit 410
judges whether or not the input cell should be
discarded based on the discard control signal 153, the
packet delimiter signal 440, and the packet discard
status information 228 extracted from the input cell in
20 the internal cell format outputted from the header
conversion circuit 132, and generates a cell discard
instruction signal 154 as described in detail in the
following (a) - (d). The cell buffer (packet discard
means) 134 selectively passes or discards the input
25 cell in accordance with the cell discard instruction
signal 154.

(a) When the packet discard status
information 228 included in the header portion of an

input cell indicates "packet under discard", the cell discard instruction signal 154 is turned on irrespective of the status of the cell discard control signal 153. With the cell discard instruction signal 154 turned on, subsequent input cells including data blocks of the same packet are sequentially discarded.

(b) When the cell discard control signal is in the "pass mode", the cell discard instruction signal 154 is turned off except for the case where an input cell falls under the condition (a). In this case, input cells are written into the buffer 134 and then supplied to the switch core unit 120.

(c) When the cell discard control signal 153 is in the "packet discard mode", the cell discard instruction signal 154 is turned on at the time the packet delimiter signal 440 is turned on. For a packet, the data block of which has partially passed, subsequent cells are not subjected to the discard processing. At the time the cell discard instruction signal 154 is turned on, the header conversion circuit 132 is provided with a header conversion table rewrite instruction 450 to set the packet discard status information 228 in the cell header in "packet under discard", such that all of subsequent cells including data blocks of the same packet are discarded under the condition (a).

(d) When the cell discard control signal 153 is in the "all cell discard mode", the cell discard

instruction signal 154 is tuned on, and an instruction 440 is issued to the header conversion circuit 132 to rewrite the header conversion table to change the packet discard status information 228 to "packet under
5 discard". In this way, input cells are sequentially discarded until the cell discard control signal 153 is changed to another mode.

While an embodiment of the present invention has been described in connection with a UBR traffic
10 class taken as an example, the present invention can be likewise applied to other traffic classes in the best effort control traffic class group, for example, an ABR traffic class. Also, the sub-class information is not particularly limited in terms of information format or
15 the like as long as it is information having unified interpretation shared among a source, switch, destination, and so on.

While a cell switch having an N (input) x N (output) configuration has been described as an example
20 in the foregoing embodiment, the cell transfer control of the present invention is also applicable to a multiplexer having a N-input x one-output configuration, a speed conversion buffer having a one-input x one-output configuration, and so on.

Also, while in the embodiment, the packet
25 discard mode has been implemented by an operation mode which recognizes a delimiter of a packet from a cell

header, passes subsequent cells of a packet, the cells of which have partially passed, and starts the discard processing from the head cell of a newly arriving packet, the packet discard mode may be modified to

5 immediately start discarding cells at the time congestion has occurred, and pass cells of a new packet and discard subsequent cells of a packet, the cells of which have been partially discarded, when the congestion is solved. Further, these packet discard

10 modes may be switched in accordance with a congestion status.

As is apparent from the foregoing embodiment, according to the present invention, a cell discard priority is declared as sub-class information in a

15 traffic class, upon setting up a call, and stored in a node such as an ATM switch and so on, for a best effort control traffic class group which has difficulties in making bandwidth reservation from a terminal unit upon setting up a call. With the cell discard priority,

20 when congestion occurs in a node, cells of connections with lower priorities are preferentially discarded, thereby making it possible to protect traffics of connections with higher priorities.

00429"07E0500

CLAIMS:

1. A cell transfer control method on an asynchronous transfer mode network, comprising the steps of:

5 when setting up a connection belonging to a particular traffic class which does not make bandwidth reservation, storing information indicative of a priority related to cell discard declared from a source unit in any of nodes in said network corresponding to
10 an identifier of said connection; and

when congestion occurs on the connection, instructing said node to perform selective discard processing on cells belonging to said particular traffic class in conformity to a predetermined discard
15 condition determined by a relationship between the status of said congestion and said priority.

2. A cell transfer control method according to claim 1, wherein:

said node is an ATM switching device
20 comprising a plurality of input ports and a plurality of output ports.

3. A cell transfer control method according to claim 1, wherein:

said node stepwisely changes a cell discard
25 priority class in accordance with the congestion status, and determines whether or not each cell belonging to said particular traffic class is discarded

in conformity to a predetermined discard condition determined by said priority and said cell discard priority class.

4. A cell transfer control method according to claim 3, wherein:

said node is an ATM switching device comprising a plurality of input ports and a plurality of output ports.

5. A cell transfer control method according to claim 3, wherein:

said node judges whether or not a data block included in a data portion of each cell of said particular traffic class is divided from the same transmission message as a data portion of a previous cell, and performs the discard processing on cells falling under the discard condition in units of transmission message.

6. A cell transfer control method according to claim 5, wherein:

said node is an ATM switching device comprising a plurality of input ports and a plurality of output ports.

7. A cell transfer control method according to claim 5, wherein:

said node starts the discard processing on cells which fall under a predetermined discard condition determined by a relationship between said congestion status and said priority, and continues the

discard processing on subsequent cells including part
of the same transmission message as data portions of
already discarded cells, even if the subsequent cells
deviate from said discard condition due to a change in
5 said congestion status.

8. A cell transfer control method according to
claim 7, wherein:

said node is an ATM switching device
comprising a plurality of input ports and a plurality
10 of output ports.

9. A cell transfer control method according to
claim 5, wherein:

said node excludes cells including data
blocks of the same transmission message as data
15 portions of previously sent cells from cells to be
discarded, within cells falling under a predetermined
discard condition determined from a relationship
between said congestion status and said priority, and
starts the discard processing from a cell including a
20 head data block of a subsequent new message.

10. A cell transfer control method according to
claim 9, wherein:

said node is an ATM switching device
comprising a plurality of input ports and a plurality
25 of output ports.

11. A packet switching device connected to a
plurality of input lines and to a plurality of output
lines for transferring each fixed length packet

(hereinafter referred to as the "cell") inputted from each input line to any output line determined by cell header information, comprising:

means, operative when setting up a connection
5 belonging to a particular traffic class which does not make bandwidth reservation, for storing information indicative of a priority related to cell discard declared from a calling unit as sub-class information corresponding to an identifier of said connection;

10 means for detecting a congestion status on each of said output lines; and

means for selectively performing discard processing on a cell belonging to said particular traffic class in conformity to a predetermined discard
15 condition determined by a relationship between a congestion status on an output line, to which the cell is to be transferred, and said priority.

12. A packet switching device connected to a plurality of input lines and to a plurality of output
20 lines for transferring each fixed length packet (hereinafter referred to as the "cell") inputted from each input line to any output line determined by cell header information, comprising:

switch means having a plurality of input
25 ports and a plurality of output ports for transferring a fixed length packet (hereinafter referred to as the "cell") inputted from each input port to any output port determined by cell header information;

input line interfaces each connected between one of said input ports and an input line;

output line interfaces each connected between one of said output ports and an output line;

5 a call control unit connected to said switch means and each of said input line interfaces for transmitting and receiving a call control cell to and from said switch means and for transmitting control information including header rewrite information to
10 each of said input interfaces; and

 congestion monitor means for detecting a congestion status of output cells on each of said output ports and notifying each of said input interfaces of a detected congestion status as
15 congestion status information,

 wherein said call control unit includes means, operative when setting a connection belonging to a particular traffic class which does not make bandwidth reservation, for notifying an input interface
20 accommodating a calling unit, which is a requestor of the connection setup, of identification information on said connection and control information including traffic class information declared by a control message from said calling unit and sub-class information
25 indicative of a priority related to cell discard; and

 each of said input interfaces includes cell discard control means for selectively discarding user

00429-07E0560

cells belonging to said particular traffic class received from each input line after the connection is set up, in conformity to a predetermined discard condition determined by a congestion status at a destination output port of said user cell revealed from said congestion status information and the priority related to cell discard notified from said call control unit.

13. A packet switching device according to claim 12, wherein:

said cell discard control means judges for each user cell belonging to said particular traffic class whether a data block included in a data portion of said cell is divided from the same transmission message as a data portion of a previous cell or divided from a new transmission message, and controls discard of user cells falling under said discard condition in units of transmission message.

14. A packet switching device according to claim 12, wherein:

said cell discard control means stores display information indicative of a cell under discard corresponding to a connection identifier of a user cell on which the discard processing has been started in conformity to said discard condition, and continues the discard processing in conformity to said display information for subsequent cells including a portion of

the same transmission message as a data portion of an already discarded cell, even if the subsequent cells deviate from said discard condition due to a change in a congestion status.

- 5 15. A packet switching device according to claim 12, wherein:

said cell discard control means includes means for excluding cells including data blocks of the same transmission message as data portions of
10 previously sent cells from cells to be discarded, within cells falling under said discard condition, and for starting the discard processing from a subsequent cell including a head data block of a new message.

- 15 16. A packet switching device according to claim 12, wherein:

said each input line interface includes header conversion means for rewriting header information of an input cell from each input line, and input buffer means for temporarily accumulating head
20 converted cells; and

said cell discard control means selectively accumulates input cells belonging to said particular traffic class in said input buffer means in conformity to said discard condition.

- 25 17. A packet switching device according to claim 16, wherein:

said cell discard control means judges for each user cell belonging to said particular traffic

00503110 021400

class whether a data block included in a data portion
of said cell is divided from the same transmission
message as a data portion of a previous cell or divided
from a new transmission message, and controls discard
5 of user cells falling under said discard condition in
units of transmission message.

18. A packet switching device according to claim
16, wherein:

said cell discard control means stores
10 display information indicative of a cell under discard
corresponding to a connection identifier of a user cell
on which the discard processing has been started in
conformity to said discard condition, and continues the
discard processing in conformity to said display
15 information for subsequent cells including a portion of
the same transmission message as a data portion of an
already discarded cell, even if the subsequent cells
deviate from said discard condition due to a change in
a congestion status.

20 19. A packet switching device according to claim
16, wherein:

said cell discard control means includes
means for excluding cells including data blocks of the
same transmission message as data portions of
25 previously sent cells from cells to be discarded,
within cells falling under said discard condition, and
for starting the discard processing from a subsequent
cell including a head data block of a new message.

20. A packet switching device according to claim 16, wherein:

said switching means includes output buffer means corresponding to said each output port, and means
5 for distributing each of user cells having a head converted by said each input line interface to either of the output buffer means specified by header information; and

said congestion monitor means detects a
10 congestion status of said output cell from an accumulation situation of user cells in said each output buffer means.

21. A packet switching device according to claim 20, wherein:

15 said cell discard control means judges for each user cell belonging to said particular traffic class whether a data block included in a data portion of said cell is divided from the same transmission message as a data portion of a previous cell or divided
20 from a new transmission message, and controls discard of user cells falling under said discard condition in units of transmission message.

22. A packet switching device according to claim 20, wherein:

25 said cell discard control means stores display information indicative of a cell under discard corresponding to a connection identifier of a user cell on which the discard processing has been started in

09503110-021400

conformity to said discard condition, and continues the discard processing in conformity to said display information for subsequent cells including a portion of the same transmission message as a data portion of an
5 already discarded cell, even if the subsequent cells deviate from said discard condition due to a change in a congestion status.

23. A packet switching device according to claim 20, wherein:

10 said cell discard control means includes means for excluding cells including data blocks of the same transmission message as data portions of previously sent cells from cells to be discarded, within cells falling under said discard condition, and
15 for starting the discard processing from a subsequent cell including a head data block of a new message.

24. A packet switching device according to claim 20, wherein:

said switch means includes a plurality of
20 output buffer means for each of said output ports, and allocates one of said output buffer means to a cell of a traffic class which guarantees a transfer rate.

25. A packet switching device according to claim 24, wherein:

25 said cell discard control means judges for each user cell belonging to said particular traffic class whether a data block included in a data portion of said cell is divided from the same transmission

004120-0720550

message as a data portion of a previous cell or divided from a new transmission message, and controls discard of user cells falling under said discard condition in units of transmission message.

- 5 26. A packet switching device according to claim 24, wherein:

10 said cell discard control means stores display information indicative of a cell under discard corresponding to a connection identifier of a user cell on which the discard processing has been started in conformity to said discard condition, and continues the discard processing in conformity to said display information for subsequent cells including a portion of the same transmission message as a data portion of an
15 already discarded cell, even if the subsequent cells deviate from said discard condition due to a change in a congestion status.

27. A packet switching device according to claim 24, wherein:

20 said cell discard control means includes means for excluding cells including data blocks of the same transmission message as data portions of previously sent cells from cells to be discarded, within cells falling under said discard condition, and
25 for starting the discard processing from a subsequent cell including a head data block of a new message.

28. A packet processing device for receiving call control information from a terminal unit when a

09503410 024400

connection is set up, said call control information including traffic class information and sub-class information indicative of a priority related to cell discard, comprising:

5 means for storing said traffic class information and said sub-class information for a connection of a particular traffic class which does not make bandwidth declaration upon initiating a call; and

 cell discard control means operative when
10 congestion occurs on said connection to selectively discard user cells by specifying cells to be discarded based on a relationship between a degree of the congestion and a priority indicated by said sub-class,

 wherein user cells are selectively discarded
15 in accordance with a connection to which each user cell belongs and a degree of congestion, even if the user cells belong to the same traffic class.

29. A packet processing device according to claim 28, wherein:

20 a header portion of each user cell includes a data block set in a data portion subsequent thereto, and delimiter information indicative of a relationship with a data unit treated by a higher rank protocol; and

 said cell discard control means specifies
25 cells to be discarded in data units of said higher rank protocol based on the delimiter information of each user cell.

004720"024400

ABSTRACT OF THE DISCLOSURE

For setting up a connection belonging to a particular traffic class which does not make bandwidth reservation, information indicative of a priority related to cell discard declared by a source unit is stored in either of nodes in an ATM network corresponding to an identifier of the connection, such that the node selectively performs discard processing on cells belonging to the particular traffic class, when congestion occurs on the connection, in conformity to a predetermined discard condition determined by a relationship between the status of the congestion and the priority. In this way, traffics can be protected for connections having higher priorities even if they do not make bandwidth reservation.

004729-024400

FIG. 1




FIG.2A




FIG.2B




FIG.2C




FIG.3





FIG.4



COMBINED DECLARATION AND POWER OF ATTORNEY
(宣誓書及び委任状)

Copy

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"PACKET SWITCHING DEVICE AND CELL TRANSFER CONTROL METHOD"

the specification of which: (check one) ☒ is attached hereto.

☐ was filed on _____
as Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended, by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me which is material to patentability in accordance with Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date earlier than that of the application(s) on which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
<u>08-012514</u> (Number)	<u>Japan</u> (Country)	<u>29 Jan., 1996</u> (Day/Month/Year Filed)	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)

(Continued on Page 2)

I hereby appoint as principal attorneys; Donald R. Antonelli, Reg. No. 20,296; David T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; Stanley A. Wal, Reg. No. 26,432; William I. Solomon, Reg. No. 28,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087; James N. Dresser, Reg. No. 22,973 and Carl I. Brundidge, Reg. No. 29,621 to prosecute and transact all business connected with this application and any related United States application and international applications. Please direct all communications to the following address:

Antonelli, Terry, Stout & Kraus
Suite 1800
1300 North Seventeenth Street
Arlington, Virginia 22209
Telephone: (703) 312-6600
Fax: (703) 312-6666

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United State Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

(Full Name)

(Signature)

Date January 20, 1997 Inventor Takeshi AIMOTO Aimoto Takeshi

Residence Sagamihara-shi, Japan Citizenship Japan

Post Office Address 4-12-902, Sagamihara-4-chome, Sagamihara-shi, Japan.

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Date _____ Inventor _____

Residence _____ Citizenship _____

Post Office Address _____

Please type a plus sign (+) inside this box → ☐

PTO/SB/122 (11-96)

Approved for use through 6/30/99. OMB 0651-0035
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

CHANGE OF CORRESPONDENCE ADDRESS *Application*

Address to:
Assistant Commissioner for Patents
Washington, D.C. 20231

Application Number	Unassigned
Filing Date	February 14, 2000
First Named Inventor	AIMOTO et al.
Group Art Unit	Unassigned
Examiner Name	Unassigned
Attorney Docket Number	500.35180CX1

Please change the Correspondence Address for the above-identified application to:



Customer Number

01-2135

Type Customer Number here

PATENT & TRADEMARK OFFICE



020457

OR

☐ Firm or
Individual Name

Address

Address

City

State

ZIP

Country

Telephone

Fax

This form cannot be used to change the data associated with a Customer Number. To change the data associated with an existing Customer Number use "Request for Customer Number Data Change" (PTO/SB/124).

I am the :



Applicant.



Assignee of record of the entire interest.
Certificate under 37 CFR 3.73(b) is enclosed.



Attorney or agent of record .

Typed or
Printed Name

David S. Lee

Registration No. 38,222

Signature

Date

February 14, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.